



**Material Safety Data Sheet**  
Golden West Synthetic Blend 5W20

|   |       |   |                      |             |
|---|-------|---|----------------------|-------------|
| <b>Material Safety Data Sheet</b><br>May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements. |       | U.S. Department of Labor<br>Occupational Safety and Health Administration<br>(Non-Mandatory Form)<br>Form Approved<br>OMB No. 1218-0072         |                      |             |
| Identity (As Used on Label and List)<br>Golden West 5W20 Synthetic Blend Motor Oil  |       | Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that. |                      |             |
| <b>Section I</b>  |       |   |                      |             |
| Manufacturer's Name<br>Golden West Packaging Co.  |       | Emergency Telephone Number<br>210-649-1401  |                      |             |
| Address (Number, street, city, state and ZIP code)<br>13598 Hwy 87 East<br>Adkins, TX 78101   |       | Telephone Number for Information<br>210-649-1401  |                      |             |
|   |       | Date Prepared<br>2006   |                      |             |
|   |       | Signature of Preparer (optional)  |                      |             |
| <b>Section II - Hazardous Ingredients/Identity Information</b>  |       |   |                      |             |
| Petroleum Hydrocarbon Mineral Oil<br>PAO Synthetic Fluid with Additives   |       | NEPA<br>Health - 0<br>Flammability - 1<br>Reactivity - 0  |                      |             |
| <b>Section III - Physical/Chemical Characteristics</b>  |       |   |                      |             |
| Boiling Point   | 600°F | Specific Gravity (H2O = 1)  | .88                  |             |
| Vapor Pressure (mm Hg.)   | NA    | Melting Point   |                      |             |
| Vapor Density (AIR = 1)   |       | Evaporation Rate (Butyl Acetate = 1)  |                      |             |
| Solubility in Water - None  |       |   |                      |             |
| Appearance and Odor - Slight Hydrocarbon odor - Pale Liquid   |       |   |                      |             |
| <b>Section IV - Fire and Explosion Hazard Data</b>  |       |   |                      |             |
| Flash Point (Method Used)   | 410°F | Flammable Limits<br>N.A.  | LEL<br>N.A.          | UEL<br>N.A. |
| Extinguishing Media - Dry chemical, foam or water spray   |       |   |                      |             |
| Special Fire Fighting Procedures - Water spray. Wear breathing apparatus.   |       |   |                      |             |
| Unusual Fire and Explosion Hazards - Could ignite under high temperatures   |       |   |                      |             |
| Style CU-FP 174 Labelmaster, Div. Of American Labelmark Co. Inc. 60646  |       |   | OSHA 174, Sept. 1985 |             |

**Section V - Reactivity Data**

Stability - Stable

Incompatibility (Materials to Avoid) - Any flammable contact material

Hazardous Decomposition or Byproducts - Hydrogen Sulide, C02 and Sulfur

|                          |                    |   |
|--------------------------|--------------------|---|
| Hazardous Polymerization | May Occur          | Conditions to Avoid - sparks, heat or burning |
|                          | Will Not Occur - X |   |

**Section VI - Health Hazard Data**

|   |                 |           |                |
|---|-----------------|-----------|----------------|
| Route(s) of Entry: eye, mouth, and skin | Inhalation? Yes | Skin? Yes | Ingestion? Yes |
|---|-----------------|-----------|----------------|

Health Hazards (Acute and Chronic) - Avoid eye and skin contact

|                          |              |                  |                 |
|--------------------------|--------------|------------------|-----------------|
| Carcinogenicity:<br>N.A. | NTP - SEEP 1 | IARC Monographs? | OSHA Regulated? |
|--------------------------|--------------|------------------|-----------------|

Signs and Symptoms of Exposure - Dizziness, breathing difficulty when fumes from burning occur.

Medical Conditions Generally Aggravated by Exposure - Skin rash

Emergency First Aid Procedures - Wash skin or affected area with soap and water.

**Section VII - Precautions for Safe Handling and Use**

Steps to be Taken in Case Material is Released or Spilled - Wear goggles when handling.

Waste Disposal Method - Neutralize with foam, detergents, and use absorbent material during cleanup. Dispose as described.

Precautions to be Taken in Handling and Storing - Keep away from extreme heat.

Other Precautions - Clean up spill, dispose of spilled product as described.

**Section VII - Control Measures**

Respiratory Protection (Specify Type) - Not required

|   |                        |                |
|---|------------------------|----------------|
| Ventilation - Store in ventilated area. | Local Exhaust - O.K.   | Special - None |
|   | Mechanical (General) - | Other -        |

Protective Gloves - Recommended

Eye Protection - Recommended

Other Protective Clothing or Equipment -

Work/Hygienic Practices - Keep product off skin and eye area. Wash thoroughly after contact.

U.S.G. P.O.: 1986-491-529/45775